

# X-7402R SPECIFICATION SHEET

## CUSTOMER HANDLING UNIT

Display	8" TFT Color display with built-in Vandal Cover Resolution: 640 x 480
Keypad	16 Numerical Keys, EPP with Triple DES 8 Function Keys
Card Reader	Dip Type (EMV 4.0 ISO 3-Track Read)

## RECEIPT PRINT UNIT

Printer Method	Direct Thermal Line Printer
Print Characters	English, Numeric, Line, Symbol, ASCII 96 Characters etc.
Paper Setting	Semi-auto loading method
Paper Width	79mm
Print Speed	100mm/sec (600 dots line/sec)
Receipt Capacity	Max 150 mm F diameter
Power Supply	DC24V
Cutter Life	300,000 cuts

## CASH DISPENSING UNIT

Cassette Capacity	2,000 notes
Dispensing Speed	Max. 5 Notes/sec
Interface	Serial (RS232C) Friction Feed Spray Dispenser
Access Direction	Rear Access
Reject Bin	Up to 200 Notes
Max Cassette Capacity	Four
Standard No of Cassettes	Two (Total: 4000 Notes)

## CONTROL UNIT

CPU	Intel PXA 255, Embedded Unit
Main Memory	64 Mb SDRAM
Fresh Memory	32M
O/S	Windows CE
Modem	RS232 Serial/Ethernet
Journal	Electronic journal
Language	Up to 7 languages

## PHYSICAL

Security	UL 291 Business Hours cabinet La Gard Electronic Combination Lock
Power	220 VAC, 7A, 50/60Hz with Noise Filter
Dimensions	450 (W) x 635 (D) x 1,392 (H) mm
Weight	120 Kg
Optional Extras	Barcode Scanner, Security Camera, Fingerprint Scanner
Maintenance Access	Front Access



**SPARK**ATM  
SYSTEMS

Tel: +27 21 418 3330  
E-mail: [info@sparkatm.co.za](mailto:info@sparkatm.co.za)  
Web: [www.sparkatm.co.za](http://www.sparkatm.co.za)